



# BERGQUIST TGR 1500A

Known as BERGQUIST TIC 1000A  
November 2018

## PRODUCT DESCRIPTION

High Performance, Value Compound for High-End Computer Processors.

<b>Technology</b>	Silicone
<b>Appearance</b>	Gray
<b>Application</b>	Thermal management, Thermally conductive adhesive
<b>Operating Temperature</b>	150 °C

## FEATURES AND BENEFITS

- High thermal performance: 0.32°C/W@ 50 psi
- Good screenability
- Room temperature storage
- No post “cure” required
- Exceptional value

BERGQUIST TGR 1500A is a high performance, thermally conductive compound intended for use as a thermal interface material between a highend computer processor and a heat sink. Other high watt density applications will also benefit from the extremely low thermal impedance of BERGQUIST TGR 1500A.

The BERGQUIST TGR 1500A compound wets-out the thermal interface surfaces and flows to produce the lowest thermal impedance. The compound requires pressure of the assembly to cause flow. The BERGQUIST TGR 1500A compound will resist dripping.

For microprocessor applications, traditional screw fastening or spring clamping methods will provide adequate force to optimize the thermal performance of BERGQUIST TGR 1500A. An optimized application would utilize the minimum volume of BERGQUIST TGR 1500A material necessary to ensure complete wet-out of both mechanical interfaces.

## TYPICAL APPLICATIONS

- High performance CPUs and GPUs

## TYPICAL PROPERTIES

### Physical Properties

Density, ASTM D792, g/cc 2.1

## Electrical Properties

Electrical Resistivity, ASTM D257, ohm-meter N/A  
The compound contains an electrically conductive filler surrounded by electrically non-conductive resin

## Thermal Properties

Thermal Conductivity , ASTM D5470, W/(m-K) 1.5

## Thermal Performance vs. Pressure

TO-220 Thermal Performance, °C/W

@ 10 psi	0.32
@ 25 psi	0.32
@ 50 psi	0.32
@ 100 psi	0.31
@ 200 psi	0.28

TO-220 performance data is provided as a reference to compare material thermal performance

## GENERAL INFORMATION

For safe handling information on this product, consult the Safety Data Sheet, (SDS).

## Directions for use

### Assembly

BERGQUIST TGR 1500A has good screenability. No solvent is used to reduce the viscosity, so no post “cure” conditioning is required

### Application Methods

1. Pre-clean heat sink and component interface with isopropyl alcohol prior to assembly or repair. Ensure heat sink is dry before applying BERGQUIST TGR 1500A
2. Dispense and/or screenprint BERGQUIST TGR 1500A compound onto the processor or heat sink surface like thermal grease (see a Bergquist Representative for application information)
3. Assemble the processor and heat sink with spring clips or constant pressure fasteners

## Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.



**Henkel Bergquist Preferred Converter**  
10135 Gottschalk Parkway  
Chagrin Falls, Ohio 44023  
sales@rico-inc.com  
+1 440-543-9209



**Conversions**

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$   
 $\text{kV/mm} \times 25.4 = \text{V/mil}$   
 $\text{mm} / 25.4 = \text{inches}$   
 $\text{N} \times 0.225 = \text{lb}$   
 $\text{N/mm} \times 5.71 = \text{lb/in}$   
 $\text{psi} \times 145 = \text{N/mm}^2$   
 $\text{MPa} = \text{N/mm}^2$   
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$   
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$   
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$   
 $\text{mPa}\cdot\text{s} = \text{cP}$

**Disclaimer****Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage:** [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

## Reference 1